

# [www.sluhcentr.ru](http://www.sluhcentr.ru)

**слуховые аппараты, решения для слуха**

**о нас каталог форум контакты**

**РОСТОВСКИЙ ЦЕНТР КОРРЕКЦИИ СЛУХА**

**г. Ростов на Дону; ул. Суворова 19**

**(863) 264-31-56; (863) 263-02-76**

**обзоры, характеристики, инструкции слуховых аппаратов**

**новости слухопротезирования события центра**

**видеотека полезная информация о слуховых аппаратах**

**Доверьте заботу о Вашем слухе профессионалам**

Центр Слухопротезирования в г. Ростове на Дону существует уже более 10 лет. Мы предлагаем полный спектр услуг, от начального определения проблемы снижения слуха до точной диагностики и подбора слухового аппарата, гарантийного, постгарантийного и сервисного обслуживания.

Новые поколения слуховых аппаратов, которые предлагает наша компания, позволяют корректировать практически любой вид тугоухости. Широкий модельный ряд - от заушных до самых маленьких внутриканальных - слуховых аппаратов позволяет успешно использовать эти слуховые аппараты, как во взрослом, так и в детском возрасте. Благодаря современным микропроцессорам и новым стратегиям обработки сигнала достигается великолепное качество звучания и оптимальная разборчивость речи в любой шумовой обстановке.

Успех слухопротезирования в нашем центре обеспечивается высоким профессионализмом наших специалистов, прошедших стажировку в ведущих центрах слухопротезирования Австрии, Германии, Швейцарии, большим выбором качественных слуховых аппаратов, использованием современного оборудования и материалов, а также чутким подходом к каждому пациенту.

**Начало на следующей странице.**

## Next™ 16 BTE Series

AutoPro3™




16 Channels, 16 Bands, Adaptive Directionality

### HEARING INSTRUMENT FEATURES

- AutoPro3™ offers faster detection and response of the 3 listening destinations and the ability to adjust comfort and clarity in all destinations
- Highly advanced feedback management that delivers more usable gain, allowing clients to enjoy the natural comforts and advantages of an open fit
- Comfort-Clarity Balance gives the client control of adaptive features (speech enhancement and noise reduction)
- AntiShock™ instantaneously reduces the level of impulse noises such as a door slam, while maintaining the quality and intelligibility of speech
- Speech enhancement LD emphasizes speech signals based on the input level
- 16 channels provide high resolution signal processing
- Adaptive directional microphone system tracks and suppresses moving noise sources, while focusing on sounds from the front
- Noise Reduction, Wind Noise Manager
- Data logging accurately records data on time spent in each program and listening destination. Volume control and Comfort-Clarity Balance changes are also logged in manual and automatic programs.
- MyMusic™ enhances the music listening experience by bringing out the rich, full tones of music
- OnBoard™ control is easily configured as a volume control or program button
- Easy-t provides automatic switching to a dedicated telephone program
- Ideal volume indicator provides a beep notification when preferred gain is reached on the volume control
- Digital volume control lever for easy control with reduced dexterity
- Up to 3 additional manual programs provide customization for individual needs and preferences
- Easy-DAI provides automatic switching to a dedicated DAI program
- Low battery warning
- Start up delay
- On/Off by opening or closing the battery door
- Can be programmed using NOAH-compatible U:fit™ and Standalone U:fit fitting software v1.4 or higher
- Choice of processing strategy, WDRC or Linear Limiting
- Battery Size: 13

### OPTIONS & ACCESSORIES





- Remote control with volume control, Comfort-Clarity Balance, program change button, and more
- Tamper-resistant volume control
- Tamper-resistant battery door
- Filtered earhook
- Slim tube coupling for instant open fittings (on Next 16, 125/60 model only)
- Choice of shell colours
- Direct Audio Input unit



Next 16 is suitable for fitting mild to severe hearing losses and can fit audiogram configurations ranging from reverse to precipitously sloping.

# Next 16 BTE Series

ANSI S3.22-1996 / IEC 118-7 2CC COUPLER TECHNICAL DATA		ANSI S3.22-1996 / IEC 118-7 2CC COUPLER TECHNICAL DATA		IEC 118-0 OES COUPLER TECHNICAL DATA			
Reference Test Frequency ANSI IEC 118-7	Next 16 Slim Tube (optional)	Next 16 (power)	Next 16 HP (high power)	Reference Test Frequency IEC 118-0	Next 16 Slim Tube (optional)	Next 16 (power)	Next 16 HP (high power)
OSPL90 Maximum HFA at RTF	HFA 2.5 kHz	HFA 1.6 kHz	HFA 1.6 kHz	OSPL90 Maximum at RTF	1.6 kHz	1.6 kHz	1.6 kHz
Full on Gain (input 50 dB) Maximum HFA at RTF	124 dB 108 dB 109 dB	125 dB 122 dB 121 dB	135 dB 128 dB 125 dB	Full on Gain (input 50 dB) Maximum at RTF	58 dB 46 dB	73 dB 64 dB	79 dB 70 dB
Basic Frequency Response Frequency Range (Hz) Reference Test Gain (ANSI 1996)	100-6300 30 dB	100-5900 45 dB	100-5600 51 dB	Basic Frequency Response Frequency Range in Hz (DIN) Reference Test Gain	100- 5700 39 dB	100- 6200 51 dB	100- 5800 58 dB
Induction Coil Sensitivity (ANSI 1996, 31.6 mA/m) HFA SPLITS STS	89 dB -1 dB	104 dB -1 dB	111 dB 0 dB	Induction Coil Sensitivity Graph shown for 31.6 mA/m at RTG at RTF (1 mA/m at Full On Gain) Maximum at RTF	99 dB 86 dB 77 dB	111 dB 90 dB 88 dB	118 dB 103 dB 96 dB
Current Drain at RTG	1.1 mA	1.2 mA	1.7 mA	Current Drain at RTG	1.1 mA	1.1 mA	1.4 mA
Typical Battery Life	265 h	245 h	170 h	Typical Battery Life	265 h	265 h	205 h
Equivalent Input Noise at RTG	28 dB	20 dB	20 dB	Equivalent Input Noise at RTG	28 dB	20 dB	20 dB
Total Harmonic Distortion at 500 Hz at 800 Hz at 1600 Hz	1% 1% 1%	4% 2% 1%	1% 1% 1%	Total Harmonic Distortion at 500 Hz at 800 Hz at 1600 Hz	2% 2% 1%	3% 2% 2%	2% 2% 2%
EMC immunity by ANSI C63.19-2001 EMC, Low Band and High Band Omni mode/Telecoil	M4/T4	M4/T4	M3/T4	EMC immunity by IEC 118-13, Field Strength 75/50 V/m, Omni mode IRIL Low/High band dB SPL	39/48	39/48	40/51



Legend: — Next 16 Power, — Next 16 High Power

### Test Conditions:

- Battery: 13
- Source: Voltage 1.3 V
- Earhook: Unfiltered
- Tubing: Length 25 mm; Inside Diameter 1.93 mm

The measurement data obtained with hearing instrument set to omni mode with all adaptive features disabled.

Domes should never be fitted on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend to use a customized ear mold. Sound pressure level of this hearing aid exceeds 132 dB SPL. We reserve the right to change specification data without notice as improvements are introduced.

